3135

Each tablet contains:
Potassium Chloride USP 600 mg

Usual Dose: See accompanying package insert for full prescribing information. Dosage must be adjusted to the individual needs of each patient

Store at 25ºC (77ºF) [See USP Controlled Room Temperature]. Protect from light and moisture. Dispense in a tight container as defined in the USP with a child resistant closure.

For Patient's Information: Be aware that the expended matrix is not absorbed and may be excreted intact in the stool.

Keep out of reach of children.

FDA approved acceptance criteria for assay differs from USP test

NDC 64380-860-08

Potassium Chloride Extended-Release Tablets, USP

8 mEq (600 mg)

Strides Pharma Inc.

1000 Tablets **Rx only**

Manufactured by:
Strides Shasun Limited
Bengaluru - 562106, India

Distributed by:
Strides Pharma Inc.,
East Brunswick, NJ 08816

Code No.:
KR/DRUGS/KTK/25/415/98

Revised: 06/2018

1032458

N 3 64380 86008 2

No Varnish Zone
[Space for Batch details coding]
window size: 42 x 17mm

Dimension : 170 x 65 mm

unwind direction of label roll

ARTWORK DETAIL LABEL

Product	**Potassium Chloride Extended-release Tablets - 600mg**				
Buyer/Country	STRIDES PHARMA INC - US	Component	CONTAINER LABEL		
Dimension	170 x 65 mm			Pack	1000's
New Item Code	**1032458**	Old Item Code	NA		
Colour Shades	PANTONE 178 C	PANTONE 340 C	BLACK	No. of Colours	3

Change Control No.	NA	Artwork Version	1.0
Design/Style	Self adhesive labels in Roll-form with Rounded Corners.		
Substrate	PSA Label Stock. 80 GSM Paper (Raflatac/Avery Dennison)16-22 GSM adhesive / 32 GSM PET (Polyester) release liner / Spot aqueous varnish.		
Special Instructions	Printing clarity should be clear and sharp.		
Autocartonator Requirements	NA		

Caution to the printer: Before processing, please ensure that the ARTWORK received for printing is exactly in line with APPROVED ARTWORK provided to you. In case of any FONTS/DESIGN are Mis-matching with the APPROVED ARTWORK, please inform PDC for further action. **DO NOT MAKE ANY CHANGE TO THE ARTWORK WITHOUT WRITTEN INSTRUCTIONS FROM PDC.**

RD/PD/003/F-08/R0